



INTERACTIVE
DISPLAYS
IRELAND



Outdoor Self-Service Kiosk

Available Sizes

21.5"

Overview

The Outdoor self service kiosk touch screen is an innovative solution that has transformed the food retail industry, providing customers with a convenient self ordering system, QR code scanner, and 24/7 availability. We understand that this technology can greatly benefit your business for outdoor usage.

Key Features



24/7 Commercial Use



Automated Self-ordering



QR & Barcode Scanner



10-Point PCAP Touch



Integrated Receipt Printer



3 Years
Warranty

IRISH
OWNED



QR Code Scanner & Thermal

features an LED light to improve reading ability and can be used to scan barcodes or QR codes in conjunction with special offers or to place orders.



Easy Maintenance & Cleaning

Tool-free maintenance is possible via the lockable front access door, allowing store staff to swap out and replace components without removing from the wall. Touch screen & barcode scanner are recessed into enclosure to wipe clean surface.



24/7 Commercial Use

As many quick service restaurants and supermarkets are open 24/7 any kiosk solution needs to be up to the task of being in continuous use.

Interactive Displays Ireland

 Dromone, Oldcastle, Co. Meath, Ireland

 0449672855  www.interactivedisplays.ie



Anti-theft Mounting Options

the kiosk can be securely mounted directly to the wall from inside the lockable door – providing an anti-theft flush fit. There is also an optional floor stand available on request when wall mounting is not possible.



Software Packages available

You can use your own software solutions or we can offer various bespoke packages on request.



Durable Protective Glass

The glass front is thermally toughened but also has a special anti-scratch 6H hardness coating. There is also a special coating on the panel which reduces annoying reflections created by external light sources.



Automated Self Ordering

allowing staff to focus more on customer service, reducing queues and waiting times as well as improving and optimising the overall customer experience. This solution is designed for the fast food sector but can also be used in a range of retail spaces.



Weatherproof

Suitable for the harshest of outdoor conditions – designed with a robust, Corrosion protected, outer casing to give protection from both the elements and the public. The outer casing has an IP65 rating which means it keeps out all airborne swarf, dust and other particles as well as being protected from any wet weather conditions; broadening the range of possible environments.



Customizable

Other sizes & colors are available on request. We also design & manufacture bespoke units with an integrated camera or double sided versions. for existing models we offer a coloured vinyl wrap service as well as custom logo & graphics



Easy Roll Replace

The till roll for the thermal printer is located in a seperate compartment so that staff can quickly & conveniently replace the roll without having to open the main access door.

Application



Specifications

21.5"

Display Area:476.64×268.11 mm(H×V)

OS Processor: V59

HDMI Input: 1

Power Type: Internal

Power Supply: AC 100 - 240 V~ (+/-10 %),50/60 Hz

Max Power : 130W

Speaker : 20W, 8Ω

Data Interface : USB HID-KBW interface, USB virtual serial port, RS-232 interface

Recognition Code System - 2D : PDF417,QR Code,Data Matrix

Recognition Code System - 1D : Code 128,EAN/UPC,Interleaved 2 of 5,Matrix 2 of 5,Industrial 25,Code 39,Codabar,Code 93,Code 32Code 11 ,MSI-Plessey,GS1-Databar

Panel:

Resolution: 1920×1080

Aspect Ratio: 16:9

Brightness (CD/M2): 1500 nits

Colour: 16.7M

Viewing Angle: 178°

Response Time: 6ms

Scanner:

Sensing Mode:CMOS

Pixel:648*488 CMOS

Reading Accuracy:≥5mil

Barcode sensitivity - tilt:±65°@ 0°Roll and 0° Skew

Barcode sensitivity - Rotation:±360°@ 0°Pitch and 0° Skew

Barcode sensitivity - Deflection:±60°@ 0°Roll and 0° Pitch

field of viewHorizontal 28°, Vertical 21.5°

Environmental:

Operating Temperature: -45°C~65°C

Storage Temperature: -50°C~70°C

Operating Humidity: 10% to 80%

Storage Humidity: 5% to 95%

Accessories:

Included:Power cable,Wifi signal booster,key,

Quality Assurance: 3 years